

## All In One Field Analyser

For measurement of several parameters in the one meter, with data logging features, Unit comes standard with all probes and will measure the following

- pH
- ORP
- DO (Dissolved Oxygen)
- Conductivity
- Resistivity
- TDS
- Temperature

### Features

- Multi parameter of 7 items (STD)  
(PH, ORP, DO, Conductivity, Resistivity, TDS & Temp)
- Auto calibration
- Data memory: Max. 100 points
- RS-232 communication and easy to read.
- CE Mark Accredited



Printer & Metal Storage Box is Included



Model	DWA-3000M						
Channel	Min. 2CH ~ Max. 7CH or Order						
Power	Meter : Adapter (Input : AC110/220V, Output : DC9V) / Ni-MH rechargeable battery 1.2 V x 6 ea (AA)						
	Printer : Alkaline battery 1.5V x 4 ea (AA)						
Items	<i>pH</i>	<i>ORP</i>	<i>DO</i>	<i>COND</i>	<i>Resistivity</i>	<i>TDS</i>	<i>Temp</i>
Range	0.00 ~ 14.00 pH	± 2000 mV	0.00 ~ 20.00 mg/L	0.00 ~ 200.00ms/cm	0.00 ~ 20.00 MΩ	0 ~ 10,000 ppm	0 ~ 99 °C
Accuracy	±0.01pH	±1 mV	±3 %	±3 %	±3 %	±3 %	
Reproducibility	±0.01 pH	±1 mV	±3 %	±3 %	±3 %	±3 %	
Response time	30sec (90%)	60sec (90%)	120sec (90%)	30sec (90%)	30sec (90%)	120sec (90%)	

### ORDERING INFORMATION

PART NUMBER	DESCRIPTION
DWA3000M	Multi Parameter Controller