

MLSS Controller Panel Mount Display



Continuous online monitoring and control for any aqueous solution to accommodate a range of sensors

The MLSS (Mixed Liquor Suspended Solids) controller (DWA-2000A-MLSS) Panel mount microprocessor has been built and designed to provide years of trouble free operation,

It is designed to be only mounted in a panel and is designed to be connected and calibrated to various levels of MLSS probes. – See probes later in this specification

This MLSS controller features fully automatic temperature compensation and accuracy to within 3% of full scale,

Control

When control of MLSS is required, this controller features a high and low relay output contact, or 4-20mA output which can be utilised to control sludge valves, WAS or RAS pumps based on plant operation design parameters

Probe Cleaning Output

The added feature that this controller has, compared to others in the market is a probe clean relay output, which can be utilised to control a solenoid for air or water jet cleaning of the probe surface. (Especially useful in the sewage & waste / industrial water plants)

Specifications	
MODEL	DWA-2000A-MLSS
Channel	Single Channel
Range	0-15,000 mg/L - Resolution 1
Power	AC 110/240v 50/60Hz
Accuracy	3% of Full Scale
Response Time	30 Seconds (90%)
Analog Output	Isolated 4-20mA DC
Digital Output	None
Relay Output	High / Low / Cleaning
Relay Voltage	Volt free 5A @24VDC / 5A @ 240VAC
Display	Measuring Value (7 Segment)
Humidity	Max 90% (Non Condensing)
IP Rating	IP54
Size	96mm(W) x 96mm(H) x 125 (D)
Installation	Panel Mount Only

ORDERING INFORMATION	
PART NUMBER	DESCRIPTION
413120001MLSS	Panel Mount MLSS Controller